

VIPER +

Textile sling for tree care work (felling operations, rigging and removal of branches): e.g. pulley/friction ring holder or redirection, redirect, etc.

SLING



DESCRIPTION

The VIPER + sling is very light, and very strong as well, as it is made of polythene. A great sling to attach to your harness.

The length is easily adjusted: up to 45 cm (1.5 ft) diameter for the 1.5 m version (4.9 ft) and up to 60 cm (2 ft) for the 2 m version (6.6 ft). It allows for optimal and fast set up of rigging works.

TECHNICAL INFORMATION

Standard	Machinery Directive 2006/42/CE
Material	100 % high modulus polythene rope (coated)
Diameter	15 mm
Construction	16-strand hollow braid (pre-streched)

Color	Grey
Elongation	4 % (at 75 % of ultimate tensile strength = 3 %)
Weight	550 g – 1.2 lb (1.5 m – 4.9 ft) 650 g – 1.4 lb (2 m – 6.6 ft)
MBS	130 kN
WLL	19 kN

REFERENCES

FTC/EVIP+1.5 length (m/ft) – 1,50 m (4.9 ft)

FTC/EVIP+2 length (m/ft) – 2 m (6.5 ft)

DOCUMENT

Declaration of conformity

Instructions 2/2

Instructions 1/2

