

# ANACONDA

20-strand rigging rope very easy to splice.

## ANACONDA ROPE



## DESCRIPTION

The ANACONDA is a 20-strand rigging rope made of coated polyester (improved resistance to abrasion). Easy to splice using our technique that maintains 100 % MBS.

Comes in 4 diameters:  
 12 mm (0.47 in) - blue  
 14 mm (0.55 in) - green  
 16 mm (0.62 in) - red  
 18 mm (0.70 in) - black

Directive- Machine 2006/42/CE Double braid made of 100% pre-stretched polyester, with polyurethane coating

Cover 50%, core 50%

## TECHNICAL INFORMATION

Diameter	Strands	Weight	MBS
12 mm (0.47 in)	20 strands	125 g/m (4.40 oz/ft)	45 kN / WLL : 6,4 kN
14 mm (0.55 in)	20 strands	175 g/m (6.17 oz/ft)	55 kN / WLL : 7,8 kN

16 mm (0.62 in) 20 strands 225 g/m (7.94 oz/ft) 67 kN / WLL : 9,5 kN

18 mm (0.70 in) 20 strands 335 g/m (11,81 oz/ft) 76 kN / WLL : 11 kN

## REFERENCES

FTC/A1240 length (m/ft) - 40 m (131.2 ft)splice - 1 splicediameter - 12 mm (0.47 in)

FTC/A1440 length (m/ft) - 40 m (131.2 ft)splice - 1 splicediameter - 14 mm (0.55 in)

FTC/A1640 length (m/ft) - 40 m (131.2 ft)splice - 1 splicediameter - 16 mm (0.62 in)

FTC/A1840 length (m/ft) - 40 m (131.2 ft)splice - 1 splicediameter - 18 mm (0.7 in)

FTC/A1250 length (m/ft) - 50 m (164 ft)splice - 1 splicediameter - 12 mm (0.47 in)

FTC/A1450 length (m/ft) - 50 m (164 ft)splice - 1 splicediameter - 14 mm (0.55 in)

FTC/A1650 length (m/ft) - 50 m (164 ft)splice - 1 splicediameter - 16 mm (0.62 in)

FTC/A1850 length (m/ft) - 50 m (164 ft)splice - 1 splicediameter - 18 mm (0.7 in)

FTC/A1265 length (m/ft) - 65 msplice - 1 splicediameter - 12 mm (0.47 in)

FTC/A1465 length (m/ft) - 65 msplice - 1 splicediameter - 14 mm (0.55 in)

FTC/A1665 length (m/ft) - 65 msplice - 1 splicediameter - 16 mm (0.62 in)

FTC/A1865 length (m/ft) - 65 msplice - 1 splicediameter - 18 mm (0.7 in)

FTC/LDT\_12 length (m/ft) - Box (~500m)splice - no splicediameter - 12 mm (0.47 in)

FTC/LDT\_14 length (m/ft) - Box (~400m)splice - no splicediameter - 14 mm (0.55 in)

FTC/LDT\_16 length (m/ft) - Box (~300m)splice - no splicediameter - 16 mm (0.62 in)

FTC/LDT\_18 length (m/ft) - Box (~300m)splice - no splicediameter - 18 mm (0.7 in)

## DOCUMENT

Declaration of conformity

Instructions

